



CURRENT TRANSFORMER,
3-PHASE FOR MOUNTING ONTO CONTACTOR AND
INSTALLING AS A SINGLE UNIT 65A / 1A,
0.1VA

General technical details:

product designation		current transformer for overload protection
Current		
• at the input / minimum	A	16
• at the input / maximum	A	65
• secondary side / maximum	A	1
Ratio input current/output current		65/1 A
Number of poles		3
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		T
Item designation / according to DIN EN 61346-2		T

Mechanical design:

Design of the electrical connection		
• secondary side		screw-type terminals
• at the input		screw-type terminals
Type of mounting		screw and snap-on mounting onto 35 mm standard mounting rail for stand-alone installation
Width	mm	90
Height	mm	122
Depth	mm	90

Ambient conditions:

Protection class IP

IP20

Ambient temperature

• during operating

°C

-25 ... +60

Certificates/approvals:

General Product Approval**For use in hazardous locations****other**[Declaration of Conformity](#)[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3UF1847-2DA00/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UF1847-2DA00**last change:**

Jan 21, 2013